

RHD

Heavy Duty Load Springs

Colour - Natural / Black Finish



WIRE

Dh	Dd	Lo	C	Maximum Life		Average Life		Code
				Pm (Kg)	Lm (mm)	Pa (Kg)	La (mm)	
11	6.5	40	0.8	9.3	11.3	11.2	13.7	RHD 11 X 040
13	8.5	55	0.4	8.1	20.8	9.7	25.2	RHD 13 X 055
15	9.5	40	1.2	14.9	12.3	18.2	15.0	RHD 15 X 040
15	9.5	50	1.0	17.9	17.5	21.6	21.2	RHD 15 X 050
16	10.5	40	1.1	15.7	14.0	19.1	17.0	RHD 16 X 040
18	12.0	85	0.6	18.6	30.8	22.5	37.4	RHD 18 X 085
19	11.0	45	3.6	35.0	9.8	42.4	11.9	RHD 19 X 045
19	11.0	50	3.1	34.3	11.2	41.6	13.6	RHD 19 X 050
19.5	9.0	83	7.7	96.4	12.6	117.0	15.3	RHD 19 X 083
20.5	10.0	35	17.3	97.1	5.6	117.9	6.8	RHD 20 X 035
20.5	9.0	90	10.0	122.6	12.3	149.6	15.0	RHD 20 X 090
21	13.5	35	1.4	14.2	10.5	17.2	12.7	RHD 21 X 035
21	12.0	40	3.3	32.0	9.8	38.9	11.9	RHD 21 X 040
22	14.5	95	0.4	14.3	34.2	17.3	41.5	RHD 22 X 095
22.5	12.0	40	10.8	82.8	7.7	100.1	9.3	RHD 22 X 040
23	14.5	45	2.6	39.3	15.0	47.6	18.2	RHD 23 X 045
23	12.5	50	7.6	83.3	11.0	100.8	13.3	RHD 23 X 050
26.5	16.0	24	13.6	67.9	5.0	82.8	6.1	RHD 26 X 024
30	13.0	70	34.8	267.8	7.7	323.4	9.3	RHD 30 X 070
32	21.0	70	2.5	58.7	23.8	71.4	28.9	RHD 32 X 070
32	16.0	150	10.6	207.1	19.6	251.4	23.8	RHD 32 X 150
34	19.0	125	6.9	153.5	22.4	186.4	27.2	RHD 34 X 125
44	25.0	130	11.0	278.1	25.2	337.6	30.6	RHD 44 X 130
44	25.0	200	6.4	277.5	43.4	337.0	52.7	RHD 44 X 200

RLD

Light Duty Load Springs

Colour - Natural / Black Finish WIRE



Dh	Dd	Lo	C	Maximum Life		Average Life		Code
				Pm (Kg)	Lm (mm)	Pa (Kg)	La (mm)	
11	6.5	40	0.8	9.3	11.3	11.2	13.7	RLD 11 X 040
13	8.5	55	0.4	8.1	20.8	9.7	25.2	RLD 13 X 055
15	9.5	40	1.2	14.9	12.3	18.2	15.0	RLD 15 X 040
15	9.5	50	1.0	17.9	17.5	21.6	21.2	RLD 15 X 050
16	10.5	40	1.1	15.7	14.0	19.1	17.0	RLD 16 X 040
18	12.0	85	0.6	18.6	30.8	22.5	37.4	RLD 18 X 085
19	11.0	45	3.6	35.0	9.8	42.4	11.9	RLD 19 X 045
19	11.0	50	3.1	34.3	11.2	41.6	13.6	RLD 19 X 050
19.5	9.0	83	7.7	96.4	12.6	117.0	15.3	RLD 19 X 083
20.5	10.0	35	17.3	97.1	5.6	117.9	6.8	RLD 20 X 035
20.5	9.0	90	10.0	122.6	12.3	149.6	15.0	RLD 20 X 090
21	13.5	35	1.4	14.2	10.5	17.2	12.7	RLD 21 X 035
21	12.0	40	3.3	32.0	9.8	38.9	11.9	RLD 21 X 040
22	14.5	95	0.4	14.3	34.2	17.3	41.5	RLD 22 X 095
22.5	12.0	40	10.8	82.8	7.7	100.1	9.3	RLD 22 X 040
23	14.5	45	2.6	39.3	15.0	47.6	18.2	RLD 23 X 045
23	12.5	50	7.6	83.3	11.0	100.8	13.3	RLD 23 X 050
26.5	16.0	24	13.6	67.9	5.0	82.8	6.1	RLD 26 X 024
30	13.0	70	34.8	267.8	7.7	323.4	9.3	RLD 30 X 070
32	21.0	70	2.5	58.7	23.8	71.4	28.9	RLD 32 X 070
32	16.0	150	10.6	207.1	19.6	251.4	23.8	RLD 32 X 150
34	19.0	125	6.9	153.5	22.4	186.4	27.2	RLD 34 X 125
44	25.0	130	11.0	278.1	25.2	337.6	30.6	RLD 44 X 130
44	25.0	200	6.4	277.5	43.4	337.0	52.7	RLD 44 X 200
48	25.0	67	65.3	411.3	6.3	496.1	7.6	RLD 48 X 067
49	29.0	50	34.4	264.6	7.7	319.6	9.3	RLD 49 X 050
55	30.0	200	16.0	482.0	30.1	586.0	36.6	RLD 55 X 200
58	39.0	50	15.4	151.1	9.8	183.5	11.9	RLD 58 X 050
63	38.0	180	12.3	371.5	30.1	451.6	36.6	RLD 63 X 180

Note : Spring beyond standard OD, ID & Length can also be manufactured (Refer Page No. 38-39)