



Ultra Load Springs Colour - Silver

PUL

Dh (mm)	Dd (mm)	Lo (mm)	C (Kg/mm)	Maximum Life		Average Life		Code
				Pm (Kg)	Lm (mm)	Pa (Kg)	La (mm)	
25	12.5	64	65.7	420	6.4	630	9.6	PUL 25 X 064
		76	56.7	431	7.6	646	11.4	PUL 25 X 076
		89	47.1	419	8.9	629	13.4	PUL 25 X 089
		102	39.8	406	10.2	608	15.3	PUL 25 X 102
		115	36.7	422	11.5	633	17.3	PUL 25 X 115
		127	33.3	423	12.7	633	19.1	PUL 25 X 127
		152	26.0	395	15.2	693	22.8	PUL 25 X 152
		178	23.5	418	17.8	626	26.7	PUL 25 X 178
		203	20.6	418	20.3	627	30.5	PUL 25 X 203
		305	13.9	424	30.5	634	45.8	PUL 25 X 305
32	16	64	109.9	703	6.4	1054	9.6	PUL 32 X 064
		76	89.1	677	7.6	1016	11.4	PUL 32 X 076
		89	73.5	654	8.9	982	13.4	PUL 32 X 089
		102	63.2	644	10.2	968	15.3	PUL 32 X 102
		115	57.1	656	11.5	985	17.3	PUL 32 X 115
		127	50.6	642	12.7	964	19.1	PUL 32 X 127
		152	41.6	632	15.2	949	22.8	PUL 32 X 152
		178	36.0	640	17.8	961	26.7	PUL 32 X 178
		203	31.0	629	20.3	944	30.5	PUL 32 X 203
		254	24.8	629	25.4	944	38.1	PUL 32 X 254
40	20	89	89.8	799	8.9	1198	13.4	PUL 40 X 089
		102	77.7	793	10.2	1189	15.3	PUL 40 X 102
		115	69.3	797	11.5	1194	17.3	PUL 40 X 115
		127	63.4	805	12.7	1208	19.1	PUL 40 X 127
		152	51.9	788	15.2	1183	22.8	PUL 40 X 152
		178	43.8	780	17.8	1168	26.7	PUL 40 X 178
		203	38.1	773	20.3	1161	30.5	PUL 40 X 203
		254	30.2	767	25.4	1150	38.1	PUL 40 X 254
		305	25.1	766	30.5	1148	45.8	PUL 40 X 305
50	25	89	143.8	1280	8.9	1920	13.4	PUL 50 X 089
		102	123.9	1264	10.2	1896	15.3	PUL 50 X 102
		115	109.8	1263	11.5	1893	17.3	PUL 50 X 115
		127	98.7	1253	12.7	1880	19.1	PUL 50 X 127
		152	82.2	1249	15.2	1874	22.8	PUL 50 X 152
		178	71.2	1267	17.8	1900	26.7	PUL 50 X 178
		203	62.4	1267	20.3	1900	30.5	PUL 50 X 203
		254	48.1	1222	25.4	1834	38.1	PUL 50 X 254
		305	39.6	1208	30.5	1810	45.8	PUL 50 X 305



Note : Spring beyond standard OD, ID & Length can also be manufactured (Refer Page No. 38-39)